

XOVA 180kW DC-Charger



Our EV charger is thoughtfully designed to be ADA-friendly, featuring an ergonomic usage height that bridges the gap between people and technology

Specifications

	Unit	UL
AC Input	Input Voltage	X 3Φ_480Vac, +10%, -15% (50/60hz)
	Input Current Rating	A Nominal: 116
	Max. Input Power	kVA 98
	Connection/ Power Grid System	- 3P+ N+ PE, TN/TT
	Power factor	X >0.99
	Efficiency	% >94
DC Output	Output Voltage	V 150 ~ 950
	Simultaneous output	- Dynamic Distribute
	Current	A CCS air cooled 300A CHAdeMO 200A/125A
Mechanical	Dimension (W x D x H)	mm/inch 32 x 26 x 75 inch
	Weight(+/-3%)	kg/lbs 1058 lbs
	Cable length	m/ft Standard:15 (Optional: 22 or 23)
Environment	Operating Temperature	°C / °F -22~-122°F
	Humidity	% 5~95%
	IP/IK ratings	- NEMA 3R IK10 (HMI IK8)
Compliance	EMC/EMI	- FCC Part 15 Subpart B ICES-003
	Safety	- UL 2202 UL 2231
Protection	Input	- OVP, UVP, OCP, OPP, OTP, SPD
	Output	- OCP, SCP, OVP, LVP, OTP, IMD
User Interface & Control	Backend Support	- OCPP 1.6 JSON, OCPP 2.0 core profile *Simultaneously connect to client & maintenance server
	Display	inch 7
	User Authentication	- QR code, RFID, Credit Card (Optional)
Communication	External	- 4G/ Wi-Fi/ Ethernet (RJ45) *Option:Wi-Fi or dual 4G