

XOVA 360kW Charging System



Our EV charger is thoughtfully designed to be ADA-friendly, featuring an ergonomic usage height that bridges the gap between people and technology

Specifications

		Unit	UL
AC Input	Input Voltage	V	3 Φ 480Vac (+10%,-15%) 50/60HZ
	Input Current Rating	A	Nominal:466
	Max. Input Power	kVA	391
	Wiring Connection/ Power Grid System	-	3P+ N+ PE, TN/TT
	Power factor	X	>0.99
	THDI	%	< 5
DC Output	Output Voltage	V	150 ~950
	Power	kW	360
	Simultaneously output mode	-	Dynamic distribution
Mechanical	Dimension (W x D x H)	mm/inch	55.12 x 31.50 x 74.80 inch
	Weight	kg/lbs	1995
Environment	Operating Temperature	°C / °F	-22~-122°F
	Humidity	%	5~95% RH, non-condensing
	IP/IK ratings	-	NEMA 3R IK10
Compliance	EMC/EMI	-	FCC Part 15 Subpart B ICES-003
	Safety	-	UL 2202 UL 2231
Protection	Input	-	OVP, UVP, OCP, OPP, OTP, SPD
	Output	-	OCP, SCP, OVP, LVP, OTP, IMD
User Interface & Control	Backend Support	-	OCPP 1.6 JSON,OCPP 2.0 core profile *Simultaneously connect to client & maintenance server
Communication	External	-	4G/ Wi-Fi/ Ethernet (RJ45)